

Roller Slewing Bearings



Basic Model			Dimensions(mm)			Installation hole size(mm)					Structure Size(mm)				Gear parameters(mm)			External tooth parameters(mm)		Parameters withinthe tooth(mm)	
No teeth	Outer teeth	Imner teeth	D	d	H	D1	D2	n	dn1 dn2	dm1 dm2	L	n1	H1	h	b	X	m	da	Z	da	Z
110.25.500	111.25.500	113.25.500	602	398	75	566	434	20	18	M16	32	4	65	10	60	0.5	5	629	123	367	74
110.25.500	112.25.500	114.25.500	602	398	75	566	434	20	18	M16	32	4	65	10	60	0.5	6	628.8	102	368.4	62
110.25.560	110.25.560	111.25.560	662	458	75	626	494	20	18	M16	32	4	65	10	30	0.5	5	689	135	427	86
110.25.560	1110.25.560	112.25.560	662	458	75	626	494	20	18	M16	32	4	65	10	30	0.5	6	688.8	112	428.4	72
110.25.630	111.25.630	113.25.630	732	528	75	696	564	24	18	M16	32	4	65	10	30	0.5	6	772.8	126	494.4	83
110.25.630	112.25.630	114.25.630	732	528	75	696	564	24	18	M16	32	4	65	10	30	0.5	8	774.4	94	491.2	62
110.25.710	111.25.710	113.25.710	812	608	75	776	644	24	18	M16	32	4	65	10	30	0.5	6	850.8	139	572.4	96
110.25.710	112.25.710	114.25.710	812	608	75	776	644	24	18	M16	32	4	65	10	30	0.5	8	854.4	104	571.2	72
110.28.800	111.28.800	113.28.800	922	678	82	878	722	30	22	M20	40	6	72	10	65	0.5	8	966.4	118	635.2	80
110.28.800	112.28.800	114.28.800	922	678	82	878	722	30	22	M20	40	6	72	10	65	0.5	10	968	94	634	64
110.28.900	111.28.900	113.28.900	1022	778	82	978	822	30	22	M20	40	6	72	10	65	0.5	8	1062.4	130	739.2	93
110.28.900	112.28.900	114.28.900	1022	778	82	978	822	30	22	M20	40	6	72	10	65	0.5	10	1068	104	734	74
110.28.1000	111.28.1000	113.28.1000	1122	878	82	1078	922	36	22	M20	40	6	72	10	65	0.5	10	1188	116	824	83
110.28.1000	112.28.1000	114.28.1000	1122	878	82	1078	922	36	22	M20	40	6	72	10	65	0.5	12	1185.6	96	820.8	69
110.28.1120	111.28.1120	113.28.1120	1242	998	82	1198	1042	36	22	M20	40	6	72	10	65	0.5	10	1298	127	944	95
110.28.1120	112.28.1120	114.28.1120	1242	998	82	1198	1042	36	22	M20	40	6	72	10	65	0.5	12	1305.6	106	940.8	79
110.32.1250	111.32.1250	113.32.1250	1390	1110	91	1337	1163	40	26	M24	48	5	81	10	75	0.5	12	1449.6	118	1048.8	88
110.32.1250	112.32.1250	114.32.1250	1390	1110	91	1337	1163	40	26	M24	48	5	81	10	75	0.5	14	1453.2	101	1041.6	75